TECHNICAL DATA SHEET

Tile Seal

Low Gloss Acrylic Tile Sealer

Description

R&D Tile Seal is a non yellowing, acrylic, water-based sealer that dries to a clear hard satin finish. Tile Seal is designed for long-term waterproofing and stain resistance of porous and semi-porous tile, stone, and concrete material.

Typical Uses

- suitable for Mexican tile, quarry tile, flagstone, and terra-cotta surfaces
- may also be used as an initial sealer on very porous stone surfaces before application of the high-gloss R&D Traffic Coat

Limitations

- Always test a small area to ensure suitability
- Surfaces are ready for light traffic 24 hours after final application.
- Full cure time is approximately 72 hours
- Apply only in temperatures between 10-25°C (50-80°F)
- Keep from freezing
- Store between 10-32°C (50-90°F)
- Sealed surface may be slippery when wet

Application

- Read all instructions thoroughly before applying
- Surface must be clean, dry and free of any sealers, repellants, efflorescence, dirt, oil, wax or grease
- Using a brush, roller or spray equipment, spread a thin coat of Tile Seal evenly over surface to be sealed
- Do not allow puddling of sealer
- A second coat may be applied approximately 20 minutes later, after first coat has dried
- If necessary to apply in direct sunlight on a warm day, slightly dampen area to be sealed with a fine spray of water prior to application

Theoretical Coverage

- 7-23 m^2 (75-250 sq.ft.) per 946ml (1 qt. US) dependent upon porosity and texture of surface

Safety Precautions

Please refer to product Safety Data sheet.

7000 Davand Drive, Mississauga, ON L5T1J5 Canada Tel: 905.795.9900 Toll Free:800.387.5703 Fax:905.795.9912
www.rdsolutions.ca www.kelmar.com