



TECHNICAL DATA SHEET

Tongue & Groove Hardwood Adhesive

Latex-based Flooring Adhesive

Description

R&D Tongue & Groove Hardwood Adhesive is water-based, non-flammable, non-toxic and is designed to bond engineered hardwood and laminated flooring together at tongue and groove when laying a floating floor system.

Typical Uses

- For bonding engineered hardwood and laminated flooring together at tongue and groove when laying a floating floor system

Features

- Non-flammable
- Non-toxic
- LEED compliant
- Meets Type II/D3 water resistance specifications.

Limitations

- For use with floating floor installations
- Do not use over unstable substrates such as chipboard and particle board.
- Plywood floors must be screwed to joists or subflooring. No deflection is permitted.
- Do not allow product to freeze
- Ensure that the adhesive and flooring products to be used are acclimatized to the temperature of the room where they will be installed

Application

- Follow the flooring manufacturer's instructions
- Apply a continuous bead of glue 3.1 mm (1/8") minimum to the top inside of all panel grooves (sides and ends)
- Fit the panels together tightly, using tapping block to ensure maximum adhesive distribution and adequate bond
- Wipe off any excess adhesive that has been squeezed out between the joints with a clean, damp cloth
- Allow glue to cure for approximately 24 hours at 21°C (70°F) before subjecting floor to heavy traffic
- CLEAN UP: Clean wet adhesive with water; remove dried adhesive with scraper or mineral spirits

Theoretical Coverage

Approximately 120 m (400 linear ft.) of a 3.1mm (1/8") bead per bottle (473ml/1 pint US).

Safety Precautions

Please refer to product Safety Data sheet.