



TECHNICAL DATA SHEET

SANLYN™ Wood Filler

Trowelable Latex Wood Filler

Description

R&D's Sanlyn™ Wood Filler is a non-shrinking, water-based hardwood filler which can be easily sanded and absorbs stain at the same rate as hardwood. It can be trowel applied to hardwood floors, and is ideal for filling gaps when laying parquet flooring.

- Apply with trowel or putty knife
- Allow to dry completely
- Sand between layers
- Fill any remaining cracks and holes
- Give a final sanding to remove any excess filler

Typical Uses

- Designed for use on all types of hardwood flooring
- Used to fill cracks, nail holes, and other imperfections found in hardwood floors

Theoretical Coverage

- Based on normal application coverage is approximately 300-500 sq.ft. per gallon

Safety Precautions

Please refer to product Safety Data sheet.

Limitations

- Always test a small area to ensure suitability
- Keep from freezing
- Store between 10-32°C (50-90°F)
- Wear a dust mask when sanding
- In damp or humid conditions, extra drying time may be required

Application

- For NEW floors, apply filler after coarse sanding and prior to medium and fine sanding
- For REFINISHING, apply filler after all old finish has been removed and prior to medium and fine sanding
- Vacuum area to remove any foreign material from cracks and voids to be filled